



Pacer Technology Super Glue's **Dishwasher Safe Super Glue (15171)** is a quick-setting, adhesive that bonds strongly and works best on:

- Glass to Glass
- Tinted Glass
- Glass to Metal
- Stained Glass
- Crystal
- Ceramics

**NOTE:** Not recommended for: food or drinking liquid contact, use in ovens, microwaves or applications over 176°F, porous materials such as paper, fabric, foam/styrofoam, foam rubber, pure bone china, polyethylene, polypropylene or teflon materials, rear view mirror applications. For Rear View Mirror installations, use Super Glue Corporation Rear View Mirror Adhesive.

**PROPERTIES:**

Initial color: Clear, transparent

Final color: Clear

Set time: 15-60 seconds

Full Strength: 24 hours

Operating Temperature Range: -65° to 180°F  
 (-54° to 82°C)

**USE INSTRUCTIONS:** NOTE: For best results, surfaces should be clean & dry and parts should mate well.

1. Protect clothing and work surfaces (aluminum foil works well) and use in well ventilated area.
2. POINT TUBE AWAY FROM FACE AND BODY. To puncture, screw nozzle and cap assembly onto tube completely. DO NOT SQUEEZE TUBE WHILE PUNCTURING.
3. Remove outer cap.
4. Apply glue sparingly (one drop per square inch) to one surface only. For optimum bonding, surfaces should be clean.
5. Do not spread glue with fingers.
6. Press pieces together for 15 to 60 seconds.
7. Clean tip and replace cap after use. Store in cool, dry place.
8. For clean-up, use acetone. **NOTE:** This may scratch some surfaces test first.

**STORAGE AND SHELF LIFE:** Replace outer cap and store upright in a cool area away from sunlight or heat sources. Stored under these conditions, a one-year shelf life can be expected.

**SAFETY AND HANDLING PRECAUTIONS**

Contains cyanoacrylate. CAUTION: Eye Irritant. Bonds skin & eyes in seconds. Use with adequate ventilation. Avoid contact with clothing as can cause burn. In case of eye contact, flush with water for 15 minutes; get medical attention for eye or internal contact. To remove from skin, soak in acetone nail polish remover & gently peel adhesive off with fingernail; water exposure will wear off residual adhesive in a few days (do not use polish remover around eye area). **KEEP OUT OF REACH OF CHILDREN.**

For more information, refer to Material Safety Data Sheet available upon request or obtain from our Pacer Technology website @ [www.supergluecorp.com](http://www.supergluecorp.com). In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 538-3091 (outside CA only) or (909) 987-0550.

Rev 1 –2016 kr

The information in this Product Data Sheet (PDS) is of a general nature based on our knowledge and experience with this product and should be used for information and consideration purposes only. The product can have a variety of different applications, as well as differing application and working conditions in your environment that are beyond our control. Therefore, this data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which Pacer Technology assumes legal responsibility. Pacer Technology strongly recommends that users of the product independently determine the suitability of the product for their use.

Pacer Technology specifically disclaims any liability for consequential or incidental damages of any kind, including profit. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.