

SAFETY DATA SHEET



Date Prepared : 06/26/2012
 MSDS No : HYDRAULIC SEALANT-GHS
 Date-Revised : 09/27/2017
 Revision No : 5

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: HYDRAULIC PNEUMATIC SEALANT (FG08020, FG08025, FG08040)

MANUFACTURER

Pacer Technology
 3281 E. Guasti Rd., Suite 260
 Ontario, CA 91761

Emergency Contact: CHEMTREC

Emergency Phone: 800-424-9300

Alternate Emergency Phone: 703-527-3887

Product Stewardship: 909-987-0550

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Irritation, Category 2

Eye Irritation, Category 2

Skin Sensitization, Category 1

Respiratory Tract Irritation, Category 3

GHS LABEL ELEMENTS

Note: If this product is a consumer product it is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.



Exclamation
 mark

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

PRECAUTIONARY STATEMENT(S)

Prevention:

P271: Use only outdoors or in a well-ventilated area.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P272: Contaminated work clothing should not be allowed out of the workplace.

Response:

SAFETY DATA SHEET



Date Prepared : 06/26/2012
 MSDS No : HYDRAULIC SEALANT-GHS
 Date-Revised : 09/27/2017
 Revision No : 5

P301+P312: IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell.
 P302+352: IF ON SKIN: Wash with plenty of soap and water.
 P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
 P362: Take off contaminated clothing.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.
 P405: Store locked up.

Disposal:

P501: Dispose of in a manner consistent with federal, state, and local regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Polyethylene Glycol Dimethacrylate	30 - 50	25852-47-5
2-HYDROXYETHYL METHACRYLATE	10 - 25	868-77-9
Polyethylene glycol ester	10 - 25	18268-70-7
Fumed Silicas	1 - 5	68909-20-6
Cumene Hydroperoxide	1 - 3	80-15-9

4. FIRST AID MEASURES

EYES: Immediately flush eyes with large quantities of water for several minutes, while holding eyelids apart. Remove contact lenses if easy to do so. Continue rinsing. Get medical attention if irritation or bonding occurs.

SKIN: Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.

INGESTION: If swallowed, do not induce vomiting. Do not give anything to drink. Obtain immediate medical attention.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes eye irritation.

SKIN: Causes skin irritation. Allergic reactions are possible.

SKIN ABSORPTION: Remove contaminated clothing and wash affected areas with soap and water. Prolonged or repeated contact can cause dermatitis in sensitive individuals. Contact a physician if irritation persists.

INGESTION: Slight to very low toxicity.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

ACUTE EFFECTS: Irritating to skin. May cause allergic skin reaction with prolonged contact.

CHRONIC EFFECTS: Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

SAFETY DATA SHEET



Date Prepared : 06/26/2012
 MSDS No : HYDRAULIC SEALANT-GHS
 Date-Revised : 09/27/2017
 Revision No : 5

5. FIRE FIGHTING MEASURES

- EXTINGUISHING MEDIA:** Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.
- HAZARDOUS COMBUSTION PRODUCTS:** Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may form when heated to decomposition.
- FIRE FIGHTING PROCEDURES:** Firefighters should wear self-contained breathing apparatus and protective clothing.
- FIRE FIGHTING EQUIPMENT:** As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.
- HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon Monoxide, carbon dioxide and unknown fumes.

6. ACCIDENTAL RELEASE MEASURES

- SMALL SPILL:** Absorb liquid and place in sealed container for disposal.
- LARGE SPILL:** This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.
- ENVIRONMENTAL PRECAUTIONS**
- WATER SPILL:** Avoid runoff into storm sewers and ditches which lead to waterways.
- LAND SPILL:** Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.
- AIR SPILL:** Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.
- SPECIAL PROTECTIVE EQUIPMENT:** Use plastic/rubber gloves, chemical splash goggles or safety glasses with side shields.

7. HANDLING AND STORAGE

- GENERAL PROCEDURES:** Use with adequate ventilation. Avoid contact with eyes, skin and clothing.
- HANDLING:** Avoid contact with skin and eyes. Wash thoroughly after handling.
- STORAGE:** Store in a cool place in original container and protect from sunlight. Keep away from sources of ignition.
- STORAGE TEMPERATURE:** Suggested storage conditions: Less than 77F/25C. Protect from freezing.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
Chemical Name	EXPOSURE LIMITS			mg/m ³
	Type		ppm	
Fumed Silicas	OSHA PEL	TWA		6 mg/m ³
	ACGIH TLV	TWA		10 mg/m ³
	Supplier OEL	TWA		3 mg/m ³
Cumene Hydroperoxide	OSHA PEL	TWA	50	245

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels.

SAFETY DATA SHEET



Date Prepared : 06/26/2012
 MSDS No : HYDRAULIC SEALANT-GHS
 Date-Revised : 09/27/2017
 Revision No : 5

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: Vinyl or rubber gloves.

RESPIRATORY: This material does not have established exposure limits. Wear a positive pressure air-supplied respirator in situations where there may be potential for airborne exposure.

PROTECTIVE CLOTHING: Wear protective clothing. Launder contaminated clothing before reuse.

WORK HYGIENIC PRACTICES: Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Paste

ODOR: Mild odor

ODOR THRESHOLD: No data available

APPEARANCE: Purple liquid.

COLOR: Purple.

pH: No data available

PERCENT VOLATILE: No data available

FLASHPOINT AND METHOD: > 93°C (200°F) Pensky-Martens CC

AUTOIGNITION TEMPERATURE: No data available

VAPOR PRESSURE: < 5 mmHg

VAPOR DENSITY: < 5

BOILING POINT: > 149°C (300°F)

FREEZING POINT: No data available

MELTING POINT: No data available

POUR POINT: No data available

SOLUBILITY IN WATER: Negligible

EVAPORATION RATE: No data available

DENSITY: No data available

SPECIFIC GRAVITY: 1.05

VISCOSITY #1: 9000 to 20000 Centipoise

(VOC): < 10 %

10. STABILITY AND REACTIVITY

REACTIVITY: Yes

HAZARDOUS POLYMERIZATION: Will not occur.

STABILITY: Stable

CONDITIONS TO AVOID: Avoid temperatures exceeding 100F/38C and incompatible materials.

POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous reactions are possible when exposed to incompatible materials such

SAFETY DATA SHEET



Date Prepared : 06/26/2012
 MSDS No : HYDRAULIC SEALANT-GHS
 Date-Revised : 09/27/2017
 Revision No : 5

as nitrates, chlorine, ammonia, strong oxidizers, alkalis, and acids

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may form when heated to decomposition.

INCOMPATIBLE MATERIALS: Strong acids and alkalis, reactive metals and strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Polyethylene Glycol Dimethacrylate	> 2000 mg/kg		
2-HYDROXYETHYL METHACRYLATE	5564 mg/kg	> 3000 mg/kg	
Cumene Hydroperoxide	382 mg/kg (rat)	133 mg/kg (rabbit)	220 ppm per 4 hr (rat)

NOTES:

INGREDIENT	LD50 and LC50 data	IMMEDIATE & DELAYED HEALTH EFFECTS
Methacrylate monomer	Not established	Allergen, Irritant
Hydroxyethyl methacrylate	Not established	Allergen, Irritant
Polyethylene glycol ester	Not established	Irritant
Fumed silicas	Not established	Irritant
Cumene hydroperoxide	Not established	Allergen, CNS, corrosive, Irritant
(contains Cumene, CAS 98-82-8, <0.1%)	Oral LD50 rat = 1,400 mg/kg; Inhalation LC50 rat, 4 hr = 8000ppm	CNS, Irritant, Lung ARC Group 2B carcinogen

SERIOUS EYE DAMAGE/IRRITATION: May cause eye irritation, skin irritation and irritation of respiratory tract.

RESPIRATORY OR SKIN SENSITISATION: May cause sensitization by skin contact.

STOT-SINGLE EXPOSURE: May cause sensitization by skin contact.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No known ecological affects of cured product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of following all Local Authority requirements for disposal.

SAFETY DATA SHEET



Date Prepared : 06/26/2012
 MSDS No : HYDRAULIC SEALANT-GHS
 Date-Revised : 09/27/2017
 Revision No : 5

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not restricted

AIR (ICAO/IATA)

SHIPPING NAME: Not restricted

VESSEL (IMO/IMDG)

SHIPPING NAME: Not restricted

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: No PRESSURE GENERATING: No REACTIVITY: No ACUTE: Yes CHRONIC: Yes

313 REPORTABLE INGREDIENTS: Section 313: Cumene hydroperoxide (CAS 80-15-9), less than 3%.

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
Cumene Hydroperoxide	1 - 3	80-15-9

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: Contains Cumene hydroperoxide (CAS 80-15-9), less than 3%.

Chemical Name	Wt.%	CERCLA RQ
Cumene Hydroperoxide	1 - 3	10

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Polyethylene Glycol Dimethacrylate	25852-47-5
2-HYDROXYETHYL METHACRYLATE	868-77-9
Polyethylene glycol ester	18268-70-7
Fumed Silicas	68909-20-6
Cumene Hydroperoxide	80-15-9

TSCA STATUS: All components are listed on or are exempt from listing on the Toxic Substances Control Act.

CALIFORNIA PROPOSITION 65: WARNING: This product can expose you to chemicals including Cumene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

16. OTHER INFORMATION

APPROVED BY: Pacer Technology Regulatory Department

PREPARED BY: Pacer Technology Regulatory Department Date-Revised: 09/27/2017

REVISION SUMMARY: This MSDS replaces the 01/30/2015 MSDS. Revised: Section 1: APPROVED BY, MSDS No,

SAFETY DATA SHEET




Date Prepared : 06/26/2012
 MSDS No : HYDRAULIC SEALANT-GHS
 Date-Revised : 09/27/2017
 Revision No : 5

PREPARED BY, TITLE. Section 2: . Section 15: CALIFORNIA PROPOSITION 65, WHMIS CLASS.

HMIS RATING

HEALTH	<input type="checkbox"/>	2
FLAMMABILITY		1
PHYSICAL HAZARD		1
PERSONAL PROTECTION		B

NFPA CODES



HMIS RATINGS NOTES: Safety glasses and gloves are recommended for usage.

MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, Pacer Technology does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.