

		<p>3281 Guasti Road, Suite 260 Ontario, CA 91761 (909) 987-0550 (800) 538-3091 Fax: (909) 987-0490 http://www.supergluecorp.com</p> <p>PRODUCT SALES SHEET: Z-42 Blue Threadlocker</p>
-----------------------------------------------------------------------------------	-----------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Pacer Technology Hobby Z-42 Blue Threadlocker (PT42) is a premium grade product used to lock or seal metal threaded components or for metal fasteners up to 3/4" in diameter. Z-42 prevents loosening due to high vibration. Parts can be disassembled with simple hand tools.

PROPERTIES: Appearance – blue liquid with mild odor.

USE INSTRUCTIONS: For best results, parts should be clean and dry. Apply a bead around the part to be bonded & assemble with a twisting motion to spread adhesive. Allow to cure 24 hours for maximum strength. Excess adhesive on outside of parts will not cure and can be removed with a solvent-soaked cloth.

STORAGE AND SHELF LIFE

Recap for storage. A one-year shelf life can be expected.

SAFETY AND HANDLING PRECAUTIONS

CAUTION: IRRITATING TO EYES AND SKIN. Contains methacrylate esters and cumene hydroperoxide. Avoid contact with eyes and skin. May cause skin dermatitis on prolonged contact with sensitive individuals. In case of eye contact, rinse immediately with plenty of water and seek medical advice. Wash skin thoroughly with soap and water after use. Seek medical advice if skin irritation persists. **KEEP OUT OF REACH OF CHILDREN.**

Airspace required in bottle to keep product liquid.

For more information, refer to Material Safety Data Sheet available upon request or obtain from our Pacer Technology website @ www.supergluecorp.com and click on the ZAP logo. In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 538-3091 (outside CA only) or call (909) 987-0550.

Rev 2 – 2016 kr

The information in this Product Data Sheet (PDS) is of a general nature based on our knowledge and experience with this product and should be used for information and consideration purposes only. The product can have a variety of different applications, as well as differing application and working conditions in your environment that are beyond our control. Therefore, this data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which Pacer Technology assumes legal responsibility. Pacer Technology strongly recommends that users of the product independently determine the suitability of the product for their use.

Pacer Technology specifically disclaims any liability for consequential or incidental damages of any kind, including profit. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.