

Pacer Technology Super Glue Contact Cement (T-CC) is a single component flexible acrylic contact adhesive that remains flexible after cure and is best used for:

- Tile
- Rubber
- Wood
- Metal
- Masonite
- Particle Board
- Plywood
- Leather
- Formica
- Plastic
- Laminates

### **PROPERTIES:**

Initial Color:	Amber	Dry Time:	30 minutes
Final Color:	Amber	Full Strength:	24 hours
Open Time:	10 minutes	Operating Temperature Range:	15° to 150°F -9° to 66°C

**USE INSTRUCTIONS:** Use in a well-ventilated area.

1. Surfaces should be clean and dry. For best results, use fine sandpaper to roughen surface.
2. Apply Contact Cement to both surfaces and wait 10 minutes.
3. Press parts together. Clamp heavier parts together. Allow 30 minutes for drying time.
4. For optimum strength in all applications, wait 24 hours before using repaired object.
5. Clean off tube or bottle top and tightly cap adhesive. Store upright and away from heat sources.

Note: Solvents may evaporate from bottle or tube if left open for prolonged periods.

### **STORAGE AND SHELF LIFE:**

Store in a cool area away from sunlight or heat. Stored under these conditions, a one-year shelf life can be expected.

### **SAFETY AND HANDLING PRECAUTIONS:**

Contains methyl ethyl ketone, hexane and ethyl acetate. Warning – liquid adhesive is extremely flammable. Harmful or fatal if swallowed. Injurious to eyes with direct contact. Avoid prolonged breathing of vapors and prolonged skin contact. Wear suitable protective clothing and gloves. Use and store in well-ventilated area away from heat, sparks or flame. In case of eye contact, flush with water for 15 minutes and seek medical advice. If swallowed, contact physician immediately and show the container label. Wash hands & skin with soap and water after use. **KEEP OUT OF REACH OF CHILDREN.**

For more information, refer to Safety Data Sheet available upon request or obtain from our Pacer Technology website at [www.supergluecorp.com](http://www.supergluecorp.com). In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 538-3091 (outside CA only) or (909) 987-0550.

Rev 3 - 2016 ksr

The information in this Product Data Sheet (PDS) is of a general nature based on our knowledge and experience with this product and should be used for information and consideration purposes only. The product can have a variety of different applications, as well as differing application and working conditions in your environment

that are beyond our control. Therefore, this data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which Pacer Technology assumes legal responsibility. Pacer Technology strongly recommends that users of the product independently determine the suitability of the product for their use.

Pacer Technology specifically disclaims any liability for consequential or incidental damages of any kind, including profit. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.