

SAFETY DATA SHEET



Date Issued : 05/10/2016
SDS No : 11710362_SY-IN12 - RESIN
Date Revised : 06/09/2021
Revision No : 13

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: SUPER GLUE INSTANT ADH BREAK OFF TIP(12) - RESIN

PRODUCT CODE: 11710362 SY-IN12 - RESIN

MANUFACTURER

Pacer Technology
 3281 E. Guasti Road, Suite 260
 Ontario, CA 91761

Emergency Contact: Chemtrec

Emergency Phone: (800) 424-9300

Customer Service: (909) 987-0550

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Irritation, Category 2
 Eye Irritation, Category 2B
 Skin sensitisation, Category 1B
 Reproductive Toxicity, Category 2

GHS LABEL

Note: If this product is a consumer product it is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.



Exclamation
mark



Health
hazard

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H315: Causes skin irritation.
 H317: May cause an allergic skin reaction.
 H319: Causes serious eye irritation.
 H361: Suspected of damaging the unborn child.

PRECAUTIONARY STATEMENTS

Prevention:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264: Wash skin and hands thoroughly after handling.
 P272: Contaminated work clothing should not be allowed out of the workplace.
 P273: Avoid release to the environment.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.
 P362: Take off contaminated clothing.
 P363: Wash contaminated clothing before reuse.
 P391: Collect spillage.

SAFETY DATA SHEET



Date Issued : 05/10/2016
SDS No : 11710362_SY-IN12 - RESIN
Date Revised : 06/09/2021
Revision No : 13

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P313: Get medical advice/attention.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

Storage:

P403+P235: Store in a well-ventilated place. Keep cool.

Disposal:

P501: Dispose of in a manner consistent with federal, state, and local regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
Epoxy resin (Bisphenol A)	90 - 100	25068-38-6

4. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

INGESTION: If swallowed, do not induce vomiting. Keep individual calm. Get medical attention and show container label.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. Get medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes eye irritation.

SKIN: Irritating to skin. May cause allergic skin reaction with prolonged contact.

SKIN ABSORPTION: None known.

INGESTION: May be irritating. Seek medical advice.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

ACUTE EFFECTS: Slightly irritating to eyes and respiratory tracts.

CHRONIC EFFECTS: Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Not Flammable

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Combustion products may include and are not limited to: Carbon monoxide, carbon dioxide and phenolics.

FIRE FIGHTING PROCEDURES: Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may form when heated to decomposition.

SAFETY DATA SHEET



Date Issued : 05/10/2016
SDS No : 11710362_SY-IN12 - RESIN
Date Revised : 06/09/2021
Revision No : 13

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: Contain spilled material if possible. Absorb with materials such as: Sand. Polypropylene fiber products. Polyethylene fiber products. Remove residual with soap and hot water. Collect in suitable and properly labeled containers. Residual can be removed with solvent. Solvents are not recommended for clean-up unless the recommended exposure guidelines and safe handling practices for the specific solvent are followed. Consult appropriate solvent Safety Data Sheet for handling information.

COMMENTS: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Use with adequate ventilation. Avoid contact with eyes, skin and clothing.

HANDLING: Avoid breathing (dust, vapor, mist, gas).

STORAGE: Store in a cool place in original container and protect from sunlight.

STORAGE TEMPERATURE: Ambient room temperature (70F/21C).

LOADING TEMPERATURE: Not Determined

LOADING/UNLOADING VISCOSITY: Not Determined

STORAGE PRESSURE: Not Determined

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:

Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: Wear rubber gloves to avoid prolonged skin contact.

RESPIRATORY: Use only in a well ventilated area.

PROTECTIVE CLOTHING: Wear rubber gloves & apron.

WORK HYGIENIC PRACTICES: Avoid contact with skin and eyes. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Viscous liquid.

ODOR: Mild odor.

ODOR THRESHOLD: Not Established

APPEARANCE: Paste.

COLOR: Green.

pH: Not Established

PERCENT VOLATILE: Not Established

FLASH POINT AND METHOD: 264°C (507°F) CC - Closed Cup

FLAMMABILITY: No data available

AUTOIGNITION TEMPERATURE: No data available

SAFETY DATA SHEET



Date Issued : 05/10/2016
 SDS No : 11710362_SY-IN12 - RESIN
 Date Revised : 06/09/2021
 Revision No : 13

VAPOR PRESSURE: No data available
VAPOR DENSITY: Not Established
BOILING POINT: No data available
FREEZING POINT: Not Established
MELTING POINT: Not Established
POUR POINT: Not Established
DECOMPOSITION TEMPERATURE: Not Established
SOLUBILITY IN WATER: 5.4 to 8.4 mg/L at 20°C (68°F)
EVAPORATION RATE: Not Established
DENSITY: 1.16 g/cm³ at 25°C (77°F)
SPECIFIC GRAVITY: 1.16
VISCOSITY #1: 10000 to 20000 mPa. s. at 25°C (77°F)
MOLECULAR WEIGHT: Not Established
(VOC): 0 g/L

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Will not occur.
STABILITY: Stable.
CONDITIONS TO AVOID: Avoid temperatures above () °F () °C.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, aldehydes, acids and other organic substances may be formed during combustion (>500°F) temperature degradation.
INCOMPATIBLE MATERIALS: Strong acids, oxidizing agents, mineral and organic bases, and especially aliphatic amines.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀
Epoxy resin (Bisphenol A)	> 2000 mg/kg (rat)	> 2000 mg/kg (rat)

DERMAL LD₅₀: 23000 mg/kg (rabbit)

ORAL LD₅₀: > 15000 mL/kg (rat)

SERIOUS EYE DAMAGE/IRRITATION: Prolonged or repeated skin contact may cause irritation.

RESPIRATORY OR SKIN SENSITISATION: May cause sensitization.

GERM CELL MUTAGENICITY:

In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

CARCINOGENICITY

IARC: Not listed.

NTP: Not listed.

OSHA: Not listed.

REPRODUCTIVE TOXICITY:

In animal studies, did not interfere with reproduction.

SAFETY DATA SHEET



Date Issued : 05/10/2016
SDS No : 11710362_SY-IN12 - RESIN
Date Revised : 06/09/2021
Revision No : 13

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Rainbow trout LC50, semi-static test, 96 h: 2 mg/L; Water flea EC50, static test, 48 h, immobilization: 1.8 mg/L; Bacteria IC50, 18 h: >42.6 mg/L.

AQUATIC TOXICITY (ACUTE)

Notes: Material is toxic to aquatic organisms (LC50 between 1 and 10 mg/L in the most sensitive species).

BIOACCUMULATION/ACCUMULATION: Bioconcentration potential is moderate (BCF 100 to 3000 or Log Pow 3 to 5).

ENVIRONMENTAL DATA: Do not flush to sewer.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with all local, state, and federal regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: NOT REGULATED PER 49 CFR 173.9

OTHER SHIPPING INFORMATION: This is Part A of a 2-part epoxy kit. When shipped with Part B, the epoxy kit may be shipped as: UN3316, CHEMICAL KIT, 9, III

AIR (ICAO/IATA)

SHIPPING NAME: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL-A EPOXY RESIN), 9, III

NOTE: This is Part A of a 2-part epoxy kit. When shipped with Part B, the epoxy kit may be shipped as: UN3316, CHEMICAL KIT, 9, III

VESSEL (IMO/IMDG)

SHIPPING NAME: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL-A EPOXY RESIN), 9, III

NOTE: This is Part A of a 2-part epoxy kit. When shipped with Part B, the epoxy kit may be shipped as: UN3316, CHEMICAL KIT, 9, III

COMMENTS: The transport information provided in this section only applies to the material formulation/itself, and is not specific to any package/configuration. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organizations to follow all applicable laws, regulations, and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

TITLE III NOTES: To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Epoxy resin (Bisphenol A)	25068-38-6

TSCA STATUS: All ingredients in this mixture are in compliance with TSCA.

SAFETY DATA SHEET



Date Issued : 05/10/2016
 SDS No : 11710362_SY-IN12 - RESIN
 Date Revised : 06/09/2021
 Revision No : 13

CALIFORNIA PROPOSITION 65: **WARNING:** This product can expose you to chemicals including Bisphenol A, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical Name	Wt. %	Listed
Epoxy resin (Bisphenol A)	90 - 100	● Female Reproductive

16. OTHER INFORMATION

APPROVED BY: Pacer Technology Regulatory Affairs Department


PREPARED BY: Pacer Technology Regulatory Affairs Department **Date Revised:** 06/09/2021

REVISION SUMMARY: This SDS replaces the 06/09/2021 SDS. Revised: **Section 1:** Date Revised, SDS No, PRODUCT CODE. **Section 2:** GHS CLASSIFICATIONS, GHS LABEL, PRECAUTIONARY STATEMENTS.

HMIS RATING

HEALTH	<input type="checkbox"/>	1
FLAMMABILITY	<input type="checkbox"/>	1
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input type="checkbox"/>	

NFPA CODES



MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, Pacer Technology does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

SAFETY DATA SHEET



Date Issued : 11/25/2013
SDS No : 11710362_SY-IN12 - HARDENER
Date Revised : 06/09/2021
Revision No : 9

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: SUPER GLUE INSTANT ADH BREAK OFF TIP(12) - HARDENER

PRODUCT CODE: 11710362_SY-IN12 - HARDENER

MANUFACTURER

Pacer Technology
3281 E. Guasti Road, Suite 260
Ontario, CA 91761

Emergency Contact: Chemtrec

Emergency Phone: (800) 424-9300

Customer Service: (909) 987-0550

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Sensitization, Category 1
Skin corrosion/Irritation, Category 1B
Serious Eye Damage, Category 1
Aquatic Hazard (Acute), Category 3

GHS LABEL

Note: If this product is a consumer product it is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.



Corrosion



Exclamation
mark

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H302: Harmful if swallowed.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.

PRECAUTIONARY STATEMENTS

Prevention:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P264: Wash skin and hands thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P363: Wash contaminated clothing before reuse.

Response:

P301+312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

SAFETY DATA SHEET



Date Issued : 11/25/2013
SDS No : 11710362_SY-IN12 - HARDENER
Date Revised : 06/09/2021
Revision No : 9

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical advice/ attention.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

Disposal:

P501: Dispose of in a manner consistent with federal, state, and local regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Mercaptan/ amine polymer system	75 - 85	
3,6-DIAZAOCTANETHYLENEDIAMINE	5 - 10	112-24-3
Bis (2-dimethylaminoethyl) Ether	1 - 5	3033-62-3

4. FIRST AID MEASURES

EYES: Flush eye with water for 15 minutes. Get medical attention.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

INGESTION: If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. Get medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes eye irritation.

SKIN: Contact causes skin irritation.

INGESTION: Ingestion of this material can cause mouth, throat, esophageal, and gastrointestinal tract irritation.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

ACUTE EFFECTS: Slightly irritating to eyes and respiratory tracts.

CHRONIC EFFECTS: Avoid contact with eyes; may cause redness, irritation and conjunctivitis.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Not Flammable

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Combustion products may include: oxides of carbon, nitrogen and sulfur; hydrogen sulfides.

FIRE FIGHTING PROCEDURES: Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

SAFETY DATA SHEET



Date Issued : 11/25/2013
SDS No : 11710362_SY-IN12 - HARDENER
Date Revised : 06/09/2021 **Revision**
No : 9

HAZARDOUS DECOMPOSITION PRODUCTS: Combustible by-products of carbon monoxide/dioxide, hydrogen sulfide and oxides of sulfur.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL:

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

LARGE SPILL:

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

LAND SPILL: None known.

AIR SPILL: None known.

GENERAL PROCEDURES: -Implement cleanup procedures.

-If in public area, keep public away and advise authorities.

-Recover by pumping (use an explosion proof or hand pump) or with a suitable absorbent.

SPECIAL PROTECTIVE EQUIPMENT: Use plastic/rubber gloves, chemical splash goggles or safety glasses with side shields.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Use with adequate ventilation. Avoid contact with eyes, skin and clothing.

HANDLING: Avoid breathing (dust, vapor, mist, gas).

STORAGE: Store in a cool place in original container and protect from sunlight.

STORAGE TEMPERATURE: Ambient room temperature (70F/21C).

LOADING TEMPERATURE: Not Established

LOADING/UNLOADING VISCOSITY: Not Established

STORAGE PRESSURE: Not Established

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

SAFETY DATA SHEET



Date Issued : 11/25/2013
 SDS No : 11710362_SY-IN12 - HARDENER
 Date Revised : 06/09/2021
 Revision No : 9

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
	EXPOSURE LIMITS			
Chemical Name	Type		ppm	mg/m³
Bis (2-dimethylaminoethyl) Ether	OSHA PEL	TWA	[1]	[1]
		STEL	[1]	[1]
	ACGIH TLV	TWA	0.05 ppm	
		STEL	0.15 ppm	
Footnotes:				
1. Not Established				

ENGINEERING CONTROLS: Use only in a well ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: Wear rubber gloves to avoid prolonged skin contact.

RESPIRATORY: Use only in a well ventilated area.

PROTECTIVE CLOTHING: Wear protective clothing. Launder contaminated clothing before reuse.

WORK HYGIENIC PRACTICES: Avoid contact with skin and eyes. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Sulfur odor.

ODOR THRESHOLD: Not Established

APPEARANCE: Pale yellow viscous liquid.

COLOR: Pale yellow colored.

pH: Not Established

PERCENT VOLATILE: Not Established

FLASH POINT AND METHOD: > 93°C (200°F) Pensky-Martens CC

FLAMMABILITY: No data available

AUTOIGNITION TEMPERATURE: No data available

VAPOR PRESSURE: No data available

VAPOR DENSITY: No data available

BOILING POINT: No data available

FREEZING POINT: No data available

MELTING POINT: No data available

POUR POINT: Not Established

DECOMPOSITION TEMPERATURE: Not Established

SOLUBILITY IN WATER: No data available

SAFETY DATA SHEET



Date Issued : 11/25/2013
SDS No : 11710362_SY-IN12 - HARDENER
Date Revised : 06/09/2021
Revision No : 9

EVAPORATION RATE: No data available
DENSITY: No data available
SPECIFIC GRAVITY: 1.12
VISCOSITY #1: 14000 to 18000 Centipoise
MOLECULAR WEIGHT: No data available
(VOC): 0 g/L

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Under normal conditons of storage and use, hazadous reactions will not occur.

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid storage near large masses of epoxy resins.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustible by-products of carbon monoxide/dioxide, hydrogen sulfide and oxides of sulfur.

INCOMPATIBLE MATERIALS: Avoid strong oxidizing agents and amines especially when hot.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀
3,6-DIAZAOCTANETHYLENEDIAMINE	2500 mg/kg (rat)	550 mg/kg (rabbit)
Bis (2-dimethylaminoethyl) Ether	2500 mg/kg (rat)	805 mg/kg (rabbit)

RESPIRATORY OR SKIN SENSITISATION: Irritating to skin. May cause allergic skin reaction with prolonged contact.

GERM CELL MUTAGENICITY: No known significant effects or critical hazards.

CARCINOGENICITY

NOTES: No known significant effects or critical hazards.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: No data available. Contact Env. Dept.

AQUATIC TOXICITY (ACUTE)

Notes: No data available. Contact Env. Dept.

BIOACCUMULATION/ACCUMULATION: No data available. Contact Env. Dept.

ENVIRONMENTAL DATA: No data available. Contact Env. Dept.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD:

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil,

SAFETY DATA SHEET



Date Issued : 11/25/2013
 SDS No : 11710362_SY-IN12 - HARDENER
 Date Revised : 06/09/2021
 Revision No : 9

waterways, drains and sewers.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: UN3267, CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (3,6-Diazaoctanethylenediamn), 8, III

OTHER SHIPPING INFORMATION: This is Part B of a 2-part epoxy kit. When shipped with Part A, the epoxy kit may be shipped as: UN3316, CHEMICAL KIT, 9, III

AIR (ICAO/IATA)

SHIPPING NAME: UN3267, CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (3,6-Diazaoctanethylenediamn), 8, III

NOTE: This is Part B of a 2-part epoxy kit. When shipped with Part A, the epoxy kit may be shipped as: UN3316, CHEMICAL KIT, 9, III

VESSEL (IMO/IMDG)

SHIPPING NAME: UN3267, CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (3,6-Diazaoctanethylenediamn), 8, III

NOTE: This is Part B of a 2-part epoxy kit. When shipped with Part A, the epoxy kit may be shipped as: UN3316, CHEMICAL KIT, 9, III

COMMENTS: The transport information provided in this section only applies to the material formulation/itself, and is not specific to any package/configuration. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organizations to follow all applicable laws, regulations, and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Mercaptan/ amine polymer system	
3,6-DIAZAOCTANETHYLENEDIAMINE	112-24-3
Bis (2-dimethylaminoethyl) Ether	3033-62-3

TSCA STATUS: All ingredients in this mixture are in compliance with TSCA.

16. OTHER INFORMATION

APPROVED BY: Pacer Technology Regulatory Department

PREPARED BY: Pacer Technology Regulatory Department **Date Revised:** 06/09/2021

REVISION SUMMARY: This SDS replaces the 08/08/2017 SDS. Revised: **Section 1:** SDS No, PRODUCT CODE. **Section 2:** GHS CLASSIFICATIONS, GHS LABEL, PRECAUTIONARY STATEMENTS. **Section 14:** AIR (ICAO/IATA) (NOTE), DOT (DEPARTMENT OF TRANSPORTATION) (OTHER SHIPPING INFORMATION), VESSEL (IMO/IMDG) (NOTE).

SAFETY DATA SHEET




Date Issued : 11/25/2013
SDS No : 11710362_SY-IN12 - HARDENER
Date Revised : 06/09/2021
Revision No : 9

HMIS RATING

HEALTH	<input type="text"/>	2
FLAMMABILITY	<input type="text"/>	1
PHYSICAL HAZARD	<input type="text"/>	0
PERSONAL PROTECTION	<input type="text"/>	

NFPA CODES



MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, Pacer Technology does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.