

Date Prepared: 11/20/2014

MSDS No: 11740112_FG06152

Date-Revised: 09/20/2017

Revision No: 3

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: ANL-77 50ML (10)

MANUFACTURER

Pacer Technology 3281 E. Guasti Rd., Suite 260 Ontario, CA 91761

Emergency Contact: CHEMTREC Emergency Phone: 800-424-9300

Alternate Emergency Phone: 703-527-3887 Product Stewardship: 909-987-0550

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Irritation, Category 2
Eye Irritation, Category 2
Target Organ Toxicity (Single exposure), Category 3
Skin Sensitization, Category 2

GHS LABEL ELEMENTS

Note: If this product is a consumer product it is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.



SIGNAL WORD: WARNING

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

PRECAUTIONARY STATEMENT(S)

Prevention:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray. P264: Wash skin and hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P362: Take off contaminated clothing.



Date Prepared: 11/20/2014

MSDS No: 11740112_FG06152

Date-Revised: 09/20/2017

Revision No: 3

Response:

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

Disposal:

P501: Dispose of in a manner consistent with federal, state, and local regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Polyethylene Glycol Dimethacrylate	25 - 60	25852-47-5
2-HYDROXYETHYL METHACRYLATE	> 22.402	868-77-9
Cumene Hydroperoxide	0.8 - 0.9	80-15-9
2,6-di-tert-butyl-p-cresol	< 5	128-37-0
Ethylene glycol	< 5	107-21-1
Maleic acid	< 5	110-16-7
Cumene	0.02 - 0.155	98-82-8
Benzoquinone	< 5	106-51-4
Acetic Acid	≤ 0.000183	64-19-7

4. FIRST AID MEASURES

EYES: Immediately flush eyes with large quantities of water for several minutes, while holding eyelids apart. Remove contact lenses if easy to do so. Continue rinsing. Get medical attention if irritation or bonding occurs.

SKIN: Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.

INGESTION: If swallowed, do not induce vomiting. Keep individual calm. Get medical attention and show container label.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes eye irritation.

SKIN: Causes skin irritation. Allergic reactions are possible.

SKIN ABSORPTION: Remove contaminated clothing and wash affected areas with soap and water. Prolonged or repeated contact can cause dermatitis in sensitive individuals. Contact a physician if irritation persists.



Date Prepared: 11/20/2014

MSDS No: 11740112_FG06152

Date-Revised: 09/20/2017

Revision No: 3

INGESTION: Slight to very low toxicity.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation. **ACUTE EFFECTS:** Irritating to skin. May cause allergic skin reaction with prolonged contact.

CHRONIC EFFECTS: Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Not Flammable

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may form

when heated to decomposition.

EXPLOSION HAZARDS: None known

FIRE FIGHTING PROCEDURES: Evacuate area and fight fire from a safe distance.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH

approved or equivalent) and full protective gear.

FIRE EXPLOSION: None known

SENSITIVE TO STATIC DISCHARGE: None known

SENSITIVITY TO IMPACT: None known

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon and nitrogen.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Absorb liquid and place in sealed container for disposal.

LARGE SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

LAND SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

GENERAL PROCEDURES: Polymerize with water. Increase ventilation to area. Solid material may be scraped from surface. **SPECIAL PROTECTIVE EQUIPMENT:** Use plastic/rubber gloves, chemical splash goggles or safety glasses with side shields.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Use with adequate ventilation. Avoid contact with eyes, skin and clothing.

HANDLING: Avoid contact with skin and eyes. Wash thoroughly after handling.

STORAGE: Store in a cool place in original container and protect from sunlight. Keep away from sources of ignition.

STORAGE TEMPERATURE: Suggested storage conditions: Less than 77F/25C. Protect from freezing.

LOADING TEMPERATURE: Not Established

LOADING/UNLOADING VISCOSITY: Not Established

STORAGE PRESSURE: Not Established

ELECTROSTATIC ACCUMULATION HAZARD: No data available



Date Prepared: 11/20/2014

MSDS No: 11740112_FG06152

Date-Revised: 09/20/2017

Revision No: 3

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
EXPOSURE LIMITS				
Chemical Name	Тур	Туре		mg/m³
Cumene Hydroperoxide	OSHA PEL	TWA	50	245
2,6-di-tert-butyl-p-cresol	ACGIH TLV	TWA		2
Ethylene glycol	ACGIH TLV	TWA	[1]	100 [1]
Cumene	OSHA PEL	TWA	50	245
	ACGIH TLV	TWA	50	246
Donza guinon o	OSHA PEL	TWA	0.1	0.4
Benzoquinone	ACGIH TLV	TWA	0.1	0.44
	OSHA PEL	TWA	10	25
Acetic Acid ACGIH TLV	ACCIH TIV	TWA	10	25
	STEL	15	37	

OSHA TABLE COMMENTS:

1. Aerosol only

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: Vinyl or rubber gloves.

RESPIRATORY: This material does not have established exposure limits. Wear a positive pressure air-supplied respirator in situations where there may be potential for airborne exposure.

PROTECTIVE CLOTHING: Not Applicable.

WORK HYGIENIC PRACTICES: Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Mild odor

ODOR THRESHOLD: No data available

APPEARANCE: Red liquid.

pH: Not Applicable

PERCENT VOLATILE: Not Applicable

FLASHPOINT AND METHOD: > 93°C (200°F) Pensky-Martens CC



Date Prepared: 11/20/2014

MSDS No: 11740112_FG06152

Date-Revised: 09/20/2017

Revision No: 3

FLAMMABLE LIMITS: No data available

AUTOIGNITION TEMPERATURE: No data available **VAPOR PRESSURE:** < 5 mmHg at 27 °C (80 °F)

VAPOR DENSITY: No data available BOILING POINT: > 149 °C (300 °F) FREEZING POINT: Not Established MELTING POINT: Not Established POUR POINT: No data available

THERMAL DECOMPOSITION: No data available

SOLUBILITY IN WATER: Negligible

EVAPORATION RATE: Not Established

DENSITY: Not Established **SPECIFIC GRAVITY:** 1.12

VISCOSITY #1: 5500 to 8000 Centipoise

(VOC): 146 g/L

10. STABILITY AND REACTIVITY

REACTIVITY: Yes

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable

CONDITIONS TO AVOID: Avoid temperatures exceeding 100F/38C and incompatible materials.

POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous reactions are possible when exposed to incompatible materials such

as nitrates, chlorine, ammonia, strong oxidizers, alkalis, and acids

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may form when heated to decomposition.

INCOMPATIBLE MATERIALS: Strong acids and alkalis, reactive metals and strong oxidizing agents.

COMMENTS: REACTIVITY: product may react if exposed to amines, inert gases, metallic salts, heat sources or oxidizers.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY



Date Prepared: 11/20/2014

MSDS No: 11740112_FG06152

Date-Revised: 09/20/2017

Revision No: 3

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Polyethylene Glycol Dimethacrylate	> 2000 mg/kg		
2-HYDROXYETHYL METHACRYLATE	5564 mg/kg	> 3000 mg/kg	
Cumene Hydroperoxide	382 mg/kg (rat)	133 mg/kg (rabbit)	220 ppm per 4 hr (rat)
2,6-di-tert-butyl-p-cresol	890 mg/kg (rat)	> 2000 mg/kg (rat)	
Ethylene glycol	> 5000 mg/kg (rat)	10626 mg/kg (rabbit)	
Maleic acid	2870 mg/kg (rat)	2620 mg/kg (rabbit)	
Cumene	> 2000 mg/kg (rat)	10578 mg/kg (rabbit)	8000 ppm per 4 hr (rat)
Benzoquinone	130 mg/kg (rat)		
Acetic Acid	6190 mg/kg		

RESPIRATORY OR SKIN SENSITISATION: May cause sensitization by skin contact.

CARCINOGENICITY

Chemical Name	IARC Status
2,6-di-tert-butyl-p-cresol	3
Benzoquinone	3

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No known ecological affects of cured product.

ECOTOXICOLOGICAL INFORMATION: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

BIOACCUMULATION/**ACCUMULATION**: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

DISTRIBUTION: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

AQUATIC TOXICITY (ACUTE): Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

CHEMICAL FATE INFORMATION: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of following all Local Authority requirements for disposal. **PRODUCT DISPOSAL:** Dispose of following all Local Authority requirements for disposal. **EMPTY CONTAINER:** Dispose of following all Local Authority requirements for disposal.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)



Date Prepared: 11/20/2014

MSDS No: 11740112_FG06152

Date-Revised: 09/20/2017

Revision No: 3

PROPER SHIPPING NAME: Not restricted

ROAD AND RAIL (ADR/RID)

PROPER SHIPPING NAME: Not restricted

AIR (ICAO/IATA)

SHIPPING NAME: Not restricted

VESSEL (IMO/IMDG)

SHIPPING NAME: Not restricted

CANADA TRANSPORT OF DANGEROUS GOODS

SHIPPING NAME: Not restricted

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Immediate (acute) health and Delayed (chronic) health hazards. FIRE: No PRESSURE GENERATING: No REACTIVITY: No ACUTE: Yes CHRONIC: Yes

313 REPORTABLE INGREDIENTS: Section 313: Cumene hydroperoxide (CAS 80-15-9), less than 3%.

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
Benzoquinone	< 5	106-51-4

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: Contains Cumene hydroperoxide (CAS 80-15-9), less than 3%.

Chemical Name	Wt.%	CERCLA RQ
Cumene Hydroperoxide	0.8 - 0.9	10
Cumene	0.02 - 0.155	5,000
Benzoquinone	< 5	10
Acetic Acid	≤ 0.000183	5,000

TSCA (TOXIC SUBSTANCE CONTROL ACT)



Date Prepared: 11/20/2014

MSDS No: 11740112_FG06152

Date-Revised: 09/20/2017

Revision No: 3

Chemical Name	CAS
Polyethylene Glycol Dimethacrylate	25852-47-5
2-HYDROXYETHYL METHACRYLATE	868-77-9
Cumene Hydroperoxide	80-15-9
2,6-di-tert-butyl-p-cresol	128-37-0
Ethylene glycol	107-21-1
Maleic acid	110-16-7
Cumene	98-82-8
Benzoquinone	106-51-4
Acetic Acid	64-19-7

TSCA STATUS: All components are listed on or are exempt from listing on the Toxic Substances Control Act.

CALIFORNIA PROPOSITION 65: WARNING: This product can expose you to chemicals including Cumene, which is known to the State of California to cause cancer, and Ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical Name	Wt.%	Listed
Ethylene glycol	< 5	Developmental Toxicity
Cumene	0.02 - 0.155	Cancer

16. OTHER INFORMATION

APPROVED BY: Pacer Technology Regulatory Department


PREPARED BY: Pacer Technology Regulatory Department Date-Revised: 09/20/2017

REVISION SUMMARY: This MSDS replaces the 01/27/2015 MSDS. Revised: Section 1: APPROVED BY, MSDS No, PREPARED BY, TITLE. Section 2: . Section 3: Wt.%. Section 5: EXPLOSION HAZARDS, FIRE EXPLOSION, FIRE FIGHTING PROCEDURES, SENSITIVE TO STATIC DISCHARGE, SENSITIVITY TO IMPACT. Section 6: AIR SPILL, GENERAL PROCEDURES, . Section 11: ACUTE, IARC, NTP, OSHA, CARCINOGENICITY, SKIN

CORROSION/IRRITATION. **Section 13:** EMPTY CONTAINER, PRODUCT DISPOSAL. **Section 15:** CALIFORNIA PROPOSITION 65, WHMIS CLASS.

HMIS RATING





HMIS RATINGS NOTES: Safety glasses and gloves are recommended for usage.

MANUFACTURER DISCLAIMER:



Date Prepared: 11/20/2014

MSDS No: 11740112_FG06152

Date-Revised: 09/20/2017

Revision No: 3

To the best of our knowledge, the information contained herein is accurate. However, Pacer Technology does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

