

| | | |
|--|--|--|
|  |  | <p>3281 - Guasti Road, Suite 260 Ontario, CA 91761 (909) 987-0550 (800) 538-3091 Fax: (909) 987-0490 http://www.supergluecorp.com</p> <p style="text-align: right;">Fix-All Adhesive</p> |
|--|--|--|

Pacer Technology Super Glue Fix-All Adhesive (T-FA) is a single component adhesive that glues, seals and repairs and is best used for:

- | | | | |
|------------|-----------|------------|------------------------|
| • Metal | • Glass | • Leather | • Vinyl |
| • Plastics | • Rubber | • Canvas | • Porous materials |
| • Ceramics | • Fabrics | • Concrete | • Non-Porous materials |
| • Wood | • Brick | • China | |

PROPERTIES:

| | |
|---|--|
| <u>Initial color:</u> Clear | <u>Handling Time:</u> 3 hours |
| <u>Final color:</u> Clear to light yellow | <u>Full Strength:</u> 24 hours |
| <u>Open Time:</u> 10 minutes | <u>Operating Temperature Range:</u> -20 ⁰ to 150 ⁰ F |
| <u>Dry Time:</u> 30 minutes | (-29 ⁰ to 66 ⁰ C) |

USE INSTRUCTIONS: Use in a well-ventilated area. Protect work surfaces.

As a glue: Apply to both surfaces and let dry 10 minutes. Press parts together. Full cure in 24 hours. For rough, uneven or very porous surfaces, apply a thick layer to both surfaces and wait 30 minutes before joining parts.

As a sealer: Fill crack or hole with extra amounts of Fix-All and allow to dry. Add additional adhesive as needed.

For repair: To repair vinyl, rubber or fabric tears, apply Fix-All with a spatula behind, through and above the tear. Hold sides together using a strong piece of tape across the tear to hold it tightly. Remove tape after 3 hours. Remove excess with rubber eraser. Note: when thick layers are required it is better to apply a number of thin coats. Allow to cure for 3 hours before handling. Full cure in 24 hours.

Notes: Solvents may evaporate from bottle or tube if left open for prolonged periods. Not recommended for Teflon, Polyethylene or Polypropylene bonding. Avoid constant submergence in water and exposure to extremely high temperatures after cure.

STORAGE AND SHELF LIFE: Store in cool area away from sunlight or heat. Stored under these conditions, a one-year shelf life can be expected.

SAFETY AND HANDLING PRECAUTIONS

Contains xylene, naphtha and ethylbenzene. DANGER: liquid adhesive is Extremely Flammable. Harmful or fatal if swallowed. Vapor harmful. Avoid breathing vapors. Use and store in well-ventilated area away from heat, sparks or flame. May cause eye/skin irritation. In case of eye contact, flush with water for 15 minutes and seek medical advice. If swallowed, contact physician immediately and show the container label. Wash hands & skin with soap and water after use. **KEEP OUT OF REACH OF CHILDREN.**

WARNING: This product contains a chemical known to the State of California to cause cancer.

For more information, refer to Material Safety Data Sheet available upon request or obtain from our Pacer Technology website @ www.supergluecorp.com. In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 538-3091 (outside CA only) or (909) 987-0550.

Rev 1 – 2016 kr

The information in this Product Data Sheet (PDS) is of a general nature based on our knowledge and experience with this product and should be used for information and consideration purposes only. The product can have a variety of different applications, as well as differing application and working conditions in your environment that are beyond our control. Therefore, this data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which Pacer Technology assumes legal responsibility. Pacer Technology strongly recommends that users of the product independently determine the suitability of the product for their use.

Pacer Technology specifically disclaims any liability for consequential or incidental damages of any kind, including profit. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.