

		<p>3281 - Guasti Road, Suite 260 Ontario, CA 91761 (909) 987-0550 (800) 538-3091 Fax: (909) 987-0490 http://www.supergluecorp.com</p> <p>Household Cement</p>
---	---	---

Pacer Technology Super Glue Household Cement (T-HCT) is a single component adhesive that can be used to repair all household items, is dishwasher safe and is best used for:

- | | | |
|------------|------------|------------------------|
| • Metal | • Plastics | • Porous materials |
| • Glass | • Rubber | • Non-Porous materials |
| • Ceramics | • Wood | |
| • China | • Jewelry | |

PROPERTIES:

Initial color: Clear

Final color: Clear

Open Time: 5 minutes

Dry Time:

30 minutes

Full Strength:

16 hours

Operating Temperature Range: 25⁰ to 125⁰F (-4⁰ to 52⁰C)

USE INSTRUCTIONS: Use in a well-ventilated area. Protect work surfaces. Clean and dry surfaces. Roughen surface for stronger bond strength.

For Non-Porous: (glass or metal) – apply to one surface to be bonded or for edge bonding apply thin film to both edges. Clamp or hold assembly for 5 minutes or until set.

For Porous: (wood or ceramic) – coat each surface and allow to dry. Apply second coat, assemble and weight or clamp parts. Allow to dry.

Full strength in 16 hours. Replace cap for storage.

STORAGE AND SHELF LIFE

Store in cool area away from sunlight or heat. Stored under these conditions, a one-year shelf life can be expected.

SAFETY AND HANDLING PRECAUTIONS

Contains methyl ethyl ketone and acetone. DANGER: Extremely flammable. Harmful if swallowed. Injurious to eyes. Vapor may be irritating. Use and store in well-ventilated area away from heat, sparks or flames. Avoid eye contact and prolonged contact with skin. In case of eye contact, flush thoroughly with water for 15 minutes and get medical attention. If swallowed seek medical advice immediately and show this container label. **KEEP OUT OF REACH OF CHILDREN.**

For more information, refer to Material Safety Data Sheet available upon request or obtain from our Pacer Technology website @ www.supergluecorp.com. In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 538-3091 (outside CA only) or (909) 987-0550.

Rev 1 – 2016 kr

The information in this Product Data Sheet (PDS) is of a general nature based on our knowledge and experience with this product and should be used for information and consideration purposes only. The product can have a variety of different applications, as well as differing application and working conditions in your environment that are beyond our control. Therefore, this data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which Pacer Technology assumes legal responsibility. Pacer Technology strongly recommends that users of the product independently determine the suitability of the product for their use.

Pacer Technology specifically disclaims any liability for consequential or incidental damages of any kind, including profit. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.