



3281 Guasti Road, Suite 260 Ontario, CA 91761 (909) 987-0550 (800) 538-3091 Fax: (909) 987-0490

http://www.supergluecorp.com

PRODUCT SALES SHEET: Zap Foam Safe Kicker

Pacer Technology Hobby Zap Foam Safe Kicker (PT28, PT52) is a solvent-based accelerator to be used with the Zap line quick set adhesives, especially Zap-O. The Zap Foam Safe Kicker formula will accelerate the cure of all cyanoacrylates, but will not attack most foam or plastic surfaces. Note: Zap Foam Safe Kicker is available in an aerosol package (PT52) – contact Pacer hobby distributor for more information.

**PROPERTIES:** Appearance: Thin, straw-colored liquid with alcohol odor.

**USE INSTRUCTIONS:** (NOTE – Not for use in cosmetic applications).

- 1. Use in a well-ventilated area with fresh air source.
- 2. Product can be applied to surfaces prior to application of adhesive to set adhesive surface.

**STORAGE AND SHELF LIFE:** Store in cool area away from sunlight or heat. Stored under these conditions, a one-year shelf life can be expected.

SAFETY AND HANDLING PRECAUTIONS: DANGER: FLAMMABLE. VAPOR HARMFUL. Contains Isopropyl alcohol. Use & store in well-ventilated area away from heat, sparks or open flames. Harmful by inhalation, in contact with eyes or skin and if swallowed. Danger of cumulative effects. Avoid prolonged breathing of vapors and skin/eye contact. Causes respiratory tract and eye irritation. Direct contact may damage eye tissues. Avoid prolonged breathing of vapor. KEEP OUT OF REACH OF CHILDREN.

## <u>PT-52 Aerosol</u>: Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

## **FIRST AID:**

Eye – flush with water for 15 minutes and seek immediate medical attention.

Inhalation – remove to fresh air & seek medial attention if breathing is difficult.

<u>Skin</u> – remove contaminated clothing, flush thoroughly with soap & water. If irritation persists, seek medical attention.

<u>Ingestion</u> – if swallowed, wash out mouth with water provided person is conscious. Contact physician.

For more information, refer to Material Safety Data Sheet available upon request or obtain from our Pacer Technology website @ <a href="www.supergluecorp.com">www.supergluecorp.com</a> and click on the ZAP logo. In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 538-3091 (outside CA only) or call (909) 987-0550.

Rev 2 - 2016 kr

The information in this Product Data Sheet (PDS) is of a general nature based on our knowledge and experience with this product and should be used for information and consideration purposes only. The product can have a variety of different applications, as well as differing application and working conditions in your environment that are beyond our control. Therefore, this data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which Pacer Technology assumes legal responsibility. Pacer Technology strongly recommends that users of the product independently determine the suitability of the product for their use.

Pacer Technology specifically disclaims any liability for consequential or incidental damages of any kind, including profit. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.