

SAFETY DATA SHEET



Date issued : 05/05/2015
 SDS number : 11720082_N88881
 Date revised : 04/10/2023
 Revision number : 5

1. Identification

Product code: 11720082_N88881

Product description: SUPER WEATHER STRIP 5OZ BOX (12)

Manufacturer / Supplier

Pacer Technology
 3281 E. Guasti Road, Suite 260
 Ontario, CA 91761

Emergency telephone number (24 hour)

CHEMTREC (800) 424-9300

Emergency contact: Chemtrec

Emergency Phone: (800) 424-9300

Customer Service: (909) 987-0550

2. Hazard identification

Classification of the substance or mixture

Health hazards:

Eye Irritation, Category 1
 Skin Irritation, Category 1

Label elements

Note: If this product is a consumer product it is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.



Flame



Skull and
crossbones



Health
hazard

Signal word: WARNING

Hazard statement(s)

H226: Flammable liquid and vapour.
 H316: Causes mild skin irritation.
 H320: Causes eye irritation.
 H333: May be harmful if inhaled.
 H336: May cause drowsiness or dizziness.

Precautionary statement(s)

Prevention:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264: Wash skin and hands thoroughly after handling.
 P271: Use only outdoors or in a well-ventilated area.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P302+352: IF ON SKIN: Wash with plenty of soap and water.
 P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

SAFETY DATA SHEET



Date issued : 05/05/2015
SDS number : 11720082_N88881
Date revised : 04/10/2023
Revision number : 5

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P332+P313: If skin irritation occurs: Get medical advice/attention.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P402+P404: Store in a dry place. Store in a closed container.

Disposal:

P501: Dispose of in a manner consistent with federal, state, and local regulations.

Emergency overview

Physical appearance: Yellow liquid with a ketone odor.

Potential health effects

Eye: Irritating to eyes.

Skin: Irritation occurs upon direct contact.

Inhalation: Remove to fresh air. Obtain immediate medical attention if breathing is difficult.

3. Composition/information on ingredients

Chemical name	% w/w	CAS No.
Methyl ethyl ketone (MEK)	5 - 20	78-93-3
Acetone	5 - 20	67-64-1
Toluene	5 - 20	108-88-3
Hexane	5 - 20	110-54-3

4. First-aid measures

Eye: Flush eye with water for 15 minutes. Get medical attention.

Skin: Remove contaminated clothing and wash affected areas with soap and water.

Ingestion: Do Not induce vomiting. Contact physician at once.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

Most important symptoms and effects, both acute and delayed

Eye: Causes eye irritation.

Skin: Causes skin irritation. Allergic reactions are possible.

Ingestion: May cause slight irritation.

Inhalation: May cause slight irritation.

Acute effects: Causes skin irritation. Allergic reactions are possible.

Chronic effects: May cause skin sensitization

5. Fire-fighting measures

Flammable class: GHS Flammable liquid, Category 3

Suitable extinguishing media: Dry chemical, foam, or carbon dioxide

SAFETY DATA SHEET



Date issued : 05/05/2015
SDS number : 11720082_N88881
Date revised : 04/10/2023
Revision number : 5

Hazardous combustion products: Carbon monoxide/dioxide and hydrocarbons

Explosion hazards: Vapors can travel to a source of ignition and flash back.

Fire fighting procedures: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

Fire fighting equipment: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

Fire explosion: Containers may rupture violently under fire temperatures. Cool containers with water if exposed to fire conditions.

Hazardous decomposition products: Carbon Monoxide, carbon dioxide, and unknown fumes.

6. Accidental release measures

Small spill: Absorb liquid and place in sealed container for disposal

Large spill: Scoop up with non-sparking tools. Place into container for disposal. Prevent run-off to sewers, streams, or other bodies of water.

Environmental precautions

Water spill: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

Land spill: Avoid runoff into storm sewers and ditches which lead to waterways.

Air spill: No data available

7. Handling and storage

Precautions for safe handling: Use in a well-ventilated area. Avoid breathing vapors. Avoid eye and skin contact. Wash hands well with soap & water after use. Keep container tightly closed when not in use. Do not cut, puncture, or weld on or near empty container.

Conditions for safe storage: Store in dry, cool area. Do not expose containers to direct sunlight.

8. Exposure controls/personal protection

SAFETY DATA SHEET



Date issued : 05/05/2015
 SDS number : 11720082_N88881
 Date revised : 04/10/2023
 Revision number : 5

Exposure controls

Control parameters				
Occupational exposure limit values				
Chemical name	Type		ppm	mg/m ³
Toluene	OSHA PEL	TWA	100 ppm ^[1]	375 mg/m ³ ^[1]
		STEL	150 ppm ^[1]	560 mg/m ³ ^[1]
	ACGIH TLV	TWA	20 ppm ^[2]	NL ^[2]
		STEL		
	Supplier OEL	TWA		
		STEL		
Hexane	OSHA PEL	TWA	500	1800
	ACGIH TLV	TWA	50	180
Footnotes: 1. OSHA 2. ACGIH-TLV				

Individual protection measures, such as personal protective equipment

Eye / face protection: Safety glasses/goggles with side shields.

Skin protection - hand protection: Rubber gloves and apron

Respiratory protection: Fresh air source or mechanical, as needed

9. Physical and chemical properties

Appearance: Yellow liquid

Color: Yellow

Odor: Characteristic

pH: No data available

Melting point: No data available

Freezing point: No data available

Initial boiling point and boiling range: 55°C (131°F)

Flash point: -26°C (-15°F)

Lower explosion limit / flammability limit: 1.2 Vol %

Upper explosion limit / flammability limit: 13 Vol %

Vapor pressure: 233.0 hPa (175 mm Hg)

Density: No data available

Relative density: 0.879

Solubility: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (logarithmic value): No data available

Auto-ignition temperature: Product is not selfigniting.

SAFETY DATA SHEET



Date issued : 05/05/2015
 SDS number : 11720082_N88881
 Date revised : 04/10/2023
 Revision number : 5

Decomposition temperature: No data available

Viscosity: No data available

Molecular weight: No data available

Percent volatiles: No data available

VOC content: 467 G/L

Notes: NOTICE: This product does not comply with the requirements of Rule 1168 of California's South Coast Air Quality Management District.

Weight Per Gallon: 7.32

VOC: 3.73 LBS/GAL (467 G/L)

568 G/L (SCAQMD RULE 1168 Method)

10. Stability and reactivity

Reactivity: Yes

Dangerous polymerization: No

Hazardous decomposition products: Carbon Monoxide, Carbon Dioxide, and hydrocarbons

Incompatible materials: Acids, Alkaline material, Amines, Strong oxidizing agents

11. Toxicological information

Acute toxicity

Chemical name	LD ₅₀ (oral) mg/kg(rat)	LD ₅₀ (dermal) mg/kg(rabbit)	LC ₅₀ (inhalation) mg/l
Methyl ethyl ketone (MEK)	2193 mg/kg	> 50000 mg/kg	
Hexane	25000 mg/kg (rat)	No data available	48000 mg/L per 4 hr (rat)

Carcinogenicity

Chemical name	IARC
Toluene	3

12. Ecological information

Other adverse effects: Possible water pollutant-avoid release to water drainage systems

13. Disposal considerations

Disposal methods: Dispose of in accordance with all local, state, and federal regulations.

14. Transport information

USA Department of Transport Regulations (DOT)

UN proper shipping name: UN1133, ADHESIVES CONTAINING FLAMMABLE LIQUID, 3, II, (LTD QTY, IP VOL LESS THAN OR EQUAL TO 1.0 L)

ICAO / IATA - air

UN proper shipping name: ID8000, CONSUMER COMMODITY, 9 (IP VOL LESS THAN OR EQUAL TO 0.5 L); or UN1133, ADHESIVES CONTAINING FLAMMABLE LIQUID, 3, II, (LTD QTY, IP VOL LESS THAN OR EQUAL TO 0.5 L)*

IMO / IMDG - International

SAFETY DATA SHEET



Date issued : 05/05/2015
 SDS number : 11720082_N88881
 Date revised : 04/10/2023
 Revision number : 5

UN proper shipping name: UN1133, ADHESIVES CONTAINING FLAMMABLE LIQUID, 3, II, (LTD QTY, IP VOL LESS THAN OR EQUAL TO 5.0 L)*

Comments: * This product may be shipped as EXCEPTED QUANTITIES OF CLASS 3, UN1133 (IP VOL LESS THAN OR EQUAL TO 0.03 L, OP VOL LESS THAN OR EQUAL TO 0.5 L)

The transport information provided in this section only applies to the material formulation/itself, and is not specific to any package/configuration. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organizations to follow all applicable laws, regulations, and rules relating to the transportation of the material.

15. Regulatory information

UNITED STATES

SARA Section 311/312 Hazard Categories

EPCRA Section 313 Toxic Chemicals

Chemical name	% w/w	CAS No.
Hexane	5 - 20	110-54-3

CERCLA Hazardous Substances and Reportable Quantities (RQ)

Chemical name	% w/w	CERCLA rq
Methyl ethyl ketone (MEK)	5 - 20	5,000
Toluene	5 - 20	1,000
Hexane	5 - 20	5,000

TSCA (The Toxic Substances Control Act)

Chemical name	CAS No.
Methyl ethyl ketone (MEK)	78-93-3
Toluene	108-88-3
Hexane	110-54-3

TSCA Status: All ingredients in this product are listed, or are exempt, for the TSCA Inventory list

California Proposition 65: ⚠ **WARNING:** This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical name	% w/w	Listed
Toluene	5 - 20	• Developmental Toxicity

General comments: This ingredient is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372: Methyl Ethyl Ketone (78-93-3), Toluene (108-88-3), N-Hexane (110-54-3)

16. Other information

Approved by: Pacer Technology Regulatory Department

SAFETY DATA SHEET



Date issued : 05/05/2015
SDS number : 11720082_N88881
Date revised : 04/10/2023
Revision number : 5

Prepared by: Pacer Technology Regulatory Department **Date revised:** 04/10/2023

Revision summary: This SDS replaces the 09/25/2017 SDS. Revised: **Section 1:** SDS number, Product code. **Section 2:** Classification of the substance or mixture, Label elements, Precautionary statement(s).

HMIS rating

Health		2
Flammability		3
Physical hazard		1
Personal protection		B

NFPA codes

