



| | | |
|---|---|--|
|  |  | <p>3281 - Guasti Road, Suite 260 Ontario, CA 91761 (909) 987-0550 (800) 538-3091 Fax: (909) 987-0490 http://www.supergluecorp.com</p> <p style="text-align: right;">Contact Cement</p> |
|---|---|--|

Pacer Technology Super Glue Contact Cement (T-CC) is a single component flexible acrylic contact adhesive that remains clear and flexible after cure and is best used for:

- | | | |
|----------|-------------|------------------|
| • Tile | • Formica | • Masonite |
| • Rubber | • Plastic | • Particle Board |
| • Wood | • Laminates | • Plywood |
| • Metal | • Metal | • Leather |

PROPERTIES:

| | |
|---|---|
| <u>Initial color:</u> Clear | <u>Dry Time:</u> 30 minutes |
| <u>Final color:</u> Clear to light yellow | <u>Full Strength:</u> 24 hours |
| <u>Open Time:</u> 10 minutes | <u>Operating Temperature Range:</u> 15 ⁰ to 150 ⁰ F (-9 ⁰ to 66 ⁰ C) |

USE INSTRUCTIONS: Use in a well-ventilated area.

1. Surfaces should be clean and dry. For best results, use fine sandpaper to roughen surface.
2. Apply Contact Cement to both surfaces and wait 10 minutes.
3. Press parts together. Clamp heavier parts together. Allow 30 minutes for drying time.
4. For optimum strength in all applications, wait 24 hours before using repaired object.
5. Clean off tube or bottle top and tightly cap adhesive. Store upright away from heat sources.

Note: Solvents may evaporate from bottle or tube if left open for prolonged periods.

STORAGE AND SHELF LIFE

Store in cool area away from sunlight or heat. Stored under these conditions, a one-year shelf life can be expected.

SAFETY AND HANDLING PRECAUTIONS

Contains methyl ethyl ketone, hexane and ethyl acetate. Warning – liquid adhesive is extremely flammable. Harmful or fatal if swallowed. Injurious to eyes with direct contact. Avoid prolonged breathing of vapors and prolonged skin contact. Wear suitable protective clothing and gloves. Use and store in well-ventilated area away from heat, sparks or flame. In case of eye contact, flush with water for 15 minutes and seek medical advice. If swallowed, contact physician immediately and show the container label. Wash hands & skin with soap and water after use. **KEEP OUT OF REACH OF CHILDREN.**

For more information, refer to Material Safety Data Sheet available upon request or obtain from our Pacer Technology website @ www.supergluecorp.com . In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 538-3091 (outside CA only) or (909) 987-0550.

Rev 2 – 2015 mkr

The data contained herein is furnished for descriptive purposes only and is believed to be reliable. Users of any products described in the data sheet have the responsibility to determine the suitability for their particular use thereof, and Pacer relies upon such users to adopt all necessary precautions to ensure the protection of property and persons against hazards involved in the use thereof.

Pacer Technology specifically makes no warranty, representation, or condition of any nature, kind or character, whether express or implied, including, but not limited to, warranties or merchantability or fitness for a particular purpose arising from the sales or use of products described in this data sheet, and none shall be implied by law. Pacer Technology specifically disclaims any liability for consequential or incidental damage of any kind, including lost profit.